

## XP-Q260H

### Thermal Receipt Printer



### Key features

- Print speeds up to 230mm/s
- Easy Maintenance: Takes 5S to update firmware only;
- User can search and manage Lan Printer directly by software;
- Steady performance: Resume from cutter jam error automatically;
- Excellent compatibility performance on different operating system;
- Energy control system to prevent printhead from overheating;
- Highly flexible for custom project;
- Hardware DIP switch available for easy setting.

### Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

# XP-Q260H

## Thermal Receipt Printer



Model	
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line(adjustable by command)
Printing speed	230 mm/s Max.
Interface	USB+Serial+Lan
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 220V, 50 ~ 60Hz Output: DC 24V/2.5A
Printer input	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.65 Kg
Dimensions	188×145×148mm ( D×W×H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150 KM
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/ Android/ Windows



Scan QR code to checkout Xprinter website for more update information.  
 Phone: (+86 756) 3895 852  
 Http://www.xprinter.com  
 Email: overseas@xprinter.net

