

RS31 series

Touch Mobile Computer



Performance	Operating system	Android 6.0
	CPU	CPU Cortex A53 Quad-core 1.3GHz
	Memory	16GB eMMC Flash/ 2GB LPDDR3 RAM
	Expansion	Micro SD card slot with SDHC support (up to 32GB)
	SIM / SAM	2 SIM slots and 1 SAM slot
	Operating power	Replaceable and rechargeable 3.85V, 2960 mAh Li-ion battery (cell 3000 mAh)
	Working hours ¹	12 hours (laser)/ 10 hours (2D imager)
	Alert	Tri-color LEDs, vibrator, speaker
Wireless communication	Interface supported	USB 2.0 OTG and charging contact
	WWAN ²	GSM/GPRS/EDGE/WCDMA/UMTS/HSDPA/HSUPA/HSPA+/LTE GSM/GPRS/EDGE: 850 / 900 / 1800 / 1900 WCDMA/UMTS/HSDPA/HSUPA: 800 / 900 / 1900 / 2100 LTE: 800 / 900 / 1800 / 2100 / 2600
	WLAN	IEEE 802.11 a/b/g/n
	WLAN security	WPA, WPA2, WEP, TKIP, AES, PEAP, TTLS, TLS, PWD, SIM
	WPAN	Bluetooth® Class II, V4.1 BLE, V2.1 with Enhanced Data Rate (EDR)
	Bluetooth® profile	GAP, SDP, HSP, SPP, GOEP, OPP, HFP, PAN, A2DP, AVRCP, GAVDP, HID, PBAP
	GPS	Built-in GPS, GLONASS, BeiDou, AGPS
	Barcode scanning	Linear imager / Laser / 2D imager
Data capture	RFID read / write	HF RFID 13.56 MHz frequency which supports ISO14443A, ISO14443B, and ISO15693 Support NFC (Peer-to-Peer, Card Reader, Card Emulation)
	Camera	Autofocus 8 megapixels with LED flash
	Display	4.7" HD 720 (W) x 1280 (H), Transmissive IPS LCD, sunlight visibility, Dragontrail™ glass
Physical characteristics	Touch panel	Capacitive touch with stylus or bare or gloved fingertip input
	Interactive Sensor Technology	Accelerometer, Light sensor, proximity sensor, e-compass
	Keypad	Dedicated scan key, 4 programmable keys, volume up and down keys, left and right trigger keys, power key
	Audio	Speaker, dual array microphones with echo and noise cancellation
	Size (LxWxH)	159 x 80 x 17.3 mm
	Weight	Under 260 g (2D imager with battery)
	Operating temperature	-20°C to 50°C / -4°F to 122°F
User environment	Storage temperature	-30°C to 70°C / -22°F to 158°F
	Humidity (non-condensed)	Operating 10% to 90% / Storage 5% to 95%
	Impact resistance	1.2 m (4 ft.) multiple drops onto concrete, 6 drops on each side / IP67 / 150 tumbles at 0.5 m With protective boot: SGS certified 1.5 m (5 ft.) multiple drops onto concrete, 6 drops on each side / IP67 / 300 tumbles at 0.5 m
	Electrostatic discharge	± 15 kV air discharge, ± 8 kV contact discharge
	Regulatory compliance	CE, RCM, NCC, JRL, TBL
		RoHS, REACH, WEEE, ErP
	Development support	Android 6.0 SDK, reader API, SAM API, HTML 5 API
Application software		Reader Configuration, Programmable keys, Mobile Deployment Suite, Software Trigger Key, Xamarin Binding, CipherLab TE, App-Lock, HTML5 (Browser and API), SOTI MobiControl, Kalipso
Accessories		Charging cradle, 4-slot battery charger, USB snap-on cable, micro USB cable, Protective boot
Warranty		1 year

1. Minimum 12/10 hours under WLAN and laser/2D scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluetooth® off / IEEE 802.11 a/b/g/n on. The test is based on one broadcasting packet per second.
2. The mobile computer has received general telecommunication certification for data communication. Please check with your local carrier for the optimum operating efficiency.

ACCESSORIES



Charging cradle



USB snap-on cable



4-slot Battery Charger



Protective Boot



HEADQUARTERS
CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec.2
 Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.cipherlab.com

CipherLab Electronics Trading
(Shanghai) Co., Ltd.
 J Room, 4F, No.728 West Yan'an Rd.
 Changning District, Shanghai
 China 200050
Tel +86 21 3368 0288
Toll Free 400 920 0285
Fax +86 21 3368 0286

CipherLab USA Inc.
 2552 Summit Ave. STE 400
 Plano, Texas, USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CipherLab Europe
 Flight Forum 40,
 5657 DB Eindhoven,
 The Netherlands
Tel +31 (0) 40 2951510